



10  
Years Warranty\*

## ANSMANN FL100W-AC

100 W ANSMANN Luminary LED spotlight with integrated 1.8m cable and CEE 7/7 ("Schuko") plug for professional use – robust and very bright

### Features

- ANSMANN Luminary BASE work floodlight with 100 W SMD LEDs and a lighting power of up to 12.000 lumens
- Extremely bright and homogeneously illuminated light for working in indoor and outdoor areas
- Integrated 180 cm long H05RN-F rubber cable for flexible use outdoors such as on construction sites, for moderate mechanical stresses.
- Splash-proof (IP65) - can be used indoors and out
- Robust aluminium and ABS housing – extremely shock-resistant
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- Versatile use thanks to the sturdy adjustment bracket - the adjustable support can be adjusted up to 80°, and the light head a full 360°!
- The spotlight is very compact when folded up thanks to the adjustable bracket - the carry handle also enables it to be comfortably carried to the desired place of use



High Power LED



Luminous flux



Protected against water jets



Beam Angle



Daylight Color



Cable length



Article number: 1600-0628

Product content: FL100W-AC, operating instructions



## Specifications

Nominal voltage	230 V
Input voltage	230V AC
Illuminant	LED
Illuminant power	100 W
Max. Lichtstrom	12.000 lumens
Protection class	IP65
Power supply	AC
IK Protection Class	IK07
Horizontal beam angle	110 °
Colour temperature	5000 K
Energy efficiency class	E
Mounting height	max. 2,99
Adjustment angle	360°
Start-up time 0-60%	0,3 s
Cable length	180 cm
Housing material	Aluminium
Color	black
Packaging	cardboard box
Operating temperature	-20 - 40 °C
Storage temperature	-25 - 80 °C